

**Serie | 4, Island cooker hood, 90 cm,
clear glass
DIG97IM50B**



**Stylish island chimney hoods perfectly
complement island hob installations.**

- **Grease filtration level:** filters out over 85% of the grease from kitchen air
- **TouchSelect control:** quick touch-control selection of desired settings and light.
- **Intensive speed setting:** removes strong kitchen odours quickly and effectively.

Technical Data

Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	691-871/691-991
Height of product, without chimney (mm) :	53
Net weight (kg) :	30.055
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	429
Boost position output recirculating (m ³ /h) :	384.0
Boost position air extraction (m ³ /h) :	732
Number of lights (Stck) :	4
Noise level (dB(A) re 1 pW) :	60
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242005099283
Connection rating (W) :	256
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation type :	Island

Optional accessories

- DHZ1230 : Adapter for roof inclination left/right
- DHZ1240 : Adapter for roof inclination front/back
- DHZ1245 : Chimney extension 1100 mm
- DHZ1255 : Chimney extension 1600 mm
- DHZ5326 : Standard odor filter (replacement)
- DHZ5365 : Standard recirculation kit
- DZZ0XX0P0 : Long Life odor filter (replacement)



Serie | 4, Island cooker hood, 90 cm, clear glass DIG97IM50B

Stylish island chimney hoods perfectly complement island hob installations.

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 429 m³/h Intensive 732 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 60 dB dB*

Special features

- TouchControl with Electronic display
- 3 power levels & intensive setting
- 4 x 1.5W LED light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 removable metal grease filter cassettes
- easy to clean Inner frame

Design

- Island chimney hood
- Clear glass
- Designed for ceiling mounted installation
- TouchControl
- Electronic control

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max. 429 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 60 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 60 dB(A) re 1 pW Intensive: 71 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 60 dB (A) re 1pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches: Extraction rate in recirculation mode: Max. normal use: 390 m³/h Intensive: 527

m³/h Noise level in recirculation mode: Max. normal use: 67 dB(A) re 1 pW Intensive: 73 dB(A) re 1 pW

- Power rating: 256 W
- Light Intensity: 502 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 71.3 kWh/year*

Optional accessories

- Recirculating kit DHZ1230

* In accordance with the EU-Regulation No 65/2014